GEM®

Break Glass call point



RoHS Compliant

Patent No.:
M328067 (Taiwan)
ZL 2007 2 0175576.7 (China)

Statement

The CP-21 series Break Glass call point, with double pole change over contacts from N/C to N/O. The main function is to override the electrical locking/release devices in case of emergency. With Key to replace glass or reset unit. With back light for L types.

Specifications

Dimensions: 87x87x55 mm
Contact Resistance: 50m£
Switch rated: 1A@125V~
Current Draw (Back light):25mA@12Vdc; 45mA@24Vdc

The double pole switch for monitoring in case of emergency when glass is broken; the contacts change from N/C to N/O..



Dimension

Unit: mm
(Common Europe Sized)

Polycarbonate
Hinged Cover

Built-in Key
(for change break glass)



Application



(Glass is broken)



Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original customer. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.

GIANNI INDUSTRIES, INC.

No. 13, Zhong Sing Road, Tu-Cheng Industrial Zone,
Tu-Cheng City, Taipei, Taiwan 23678
Tel: 886-2 2267 7986 / Fax: 886-2 2267 9876
E-Mail: info@gianni.com.tw
Website: gianni.tw

Copyright 2008 Gianni industries, inc. All rights reserved.

DM-CA-CP-21 Ver. C Published on 2008.04.29

The products are manufactured under an ISO 9001 & QC 080000 Certified Quality Management Program environment back its product quality, performance and commitment to customer satisfaction.